



# NETX Smart Router Series

## Key features

- High-performance open-source routing
- Comprehensive BGP, OSPF and IPv6 support
- Carrier Grade NAT
- DDoS protection mechanisms
- Rich set of QoS mechanisms
- Clustering and High Availability
- Advanced CLI configuration using netc

## Product overview

The NETX Smart Router Series were jointly developed with Brno University of Technology to provide high-performance and open-source routing platform. Due to rich set of routing features and high-performance routing, these routers are ideal for deployment as an aggregation network device on the network edge. NETX routers are designed to handle several full BGP feeds and provides CGN and traffic shaping capabilities in the same time. The operating system is based on GNU/Linux which allows easy extensibility and adaptation to various networking tasks.

In addition, the NETX Smart Router Series features robust configuration API that can be integrated to corporate automatisated NetOPS processes.

# Features and benefits

## Quality of Service (QoS)

- Committed Access Rate (CAR) and line rate traffic policing
- FIFO, PQ, CQ, WFQ, CBQ, and RTPQ congestion management
- Weighted random early detection (WRED) and Random early detection (RED) congestion avoidance
- API for easy integration with customer's information system

## Layer 3 services

- Dynamic Host Configuration Protocol (DHCP) for IPv4 and IPv6 protocols
- DHCPv4 and DHCPv6 Relay agent with client link-layer identifier insertion
- Domain Name System (DNS) with DNSSEC support
- Router Advertisement daemon for IPv6 Stateless address configuration
- Captive portal for users redirection

## Layer 3 routing

- Static IPv4 and IPv6 routing
- Distance vector routing protocols - RIP, RIPv2, RIPv6 and Babel
- OSPF, OSPFv3 link state routing protocols for IPv4 and IPv6 with ECMP, NSSA and MD5 authentication
- BGPv4 with support for Multiprotocol BGP, MD5 authentication, incremental updates and extensive policies to increase flexibility in large networks
- Policy based routing (PBR) for IPv4 and IPv6 to adapt routing policies to business needs; supports ACLs, IP prefix, AS paths, community lists, and aggregate policies
- Virtual Routing and Forwarding (VRF) support provides separation of the routing table per customer

## Management

- Industry-standard CLI reduces training needs and increases productivity in multivendor installations
- RESTful API for easy integration with automation processes
- SNMPv1, v2 and v3 provides complete support of SNMP protocol
- Network Time Protocol (NTP) for clock synchronisation
- Rich set of debug utilities - ping, traceroute, tracepath, mtr, possibility to sniff network traffic
- Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) protocols for maintaining IPv4 and IPv6 multicast groups
- Remote management using Secure shell security protocol

## High Availability

- Virtual Router Redundancy Protocol (VRRP) with milliseconds timers for fast convergence when links fail, ensuring high network availability
- Redundant design of main processing unit and power supply
- Smart Clustering for easy configuration and management

## Carrier Grade NAT

- Large scale network translation for preserving IPv4 address space
- Extensive logging support to keep information about user identity
- 5-tuple sessions help to accommodate larger number of customer per IPv4 address

# Features and benefits

## VxLAN

- MAC-in-UDP technology that provides Layer 2 connectivity between distant network sites across an IP network
- VXLAN L2 and L3 gateway support for up to 4k tunnels

## DDoS Protection

- BGP Flowspec support to connect NETX router with DDoS detection devices
- Remote Trigger Blackhole community support for mitigation DDoS attack
- Unicast Reverse Path Forwarding (uRPF) to filter spoofed IP addresses according Best Current Practise Document BCP38
- Hardware DDoS Mitigation based on filtration rules in network interface card; support up to 10 000 prefixes (depends on platform)

## Security

- Extended Access control lists (ACLs); Provide L3/L4 filtering based on source or destination IPv4/IPv6 address, IPv4/IPv6 subnet, source or destination TCP/UDP port number and other fields in IP or TCP/UDP header
- Secure Shell (SSH) for encryption remote connection of all transmitted data and secure remote CLI access over IP networks
- RADIUS - management security administration by using a password authentication server

## Multicast

- Internet Group Management Protocol (IGMP) to maintain multicast groups; supports v1, v2, and v3 and Source-Specific Multicast (SSM)
- Multicast Listener Discovery (MLD) protocol for maintaining IPv6 multicast groups
- Easy manipulating with multicast routes in Linux kernel
- Support both IPv4 and IPv6 multicast routing
- IGMP and MLD snooping; optimises multicast traffic flow to necessary ports

## API

- RESTful API for configuration and management; easy integration with custom NetOPS processes in your company
- Different frontends available (CLI, HTTP, custom)
- Industry Standard CLI syntax available; CLI benefits from standard GNU/Linux readline capabilities – powerful shortcuts and filtration provides faster configuration of networking tasks
- Allows directly and simply execute a command or configuration change
- Commit feature for safe configuration rollback

## MPLS

- Multiprotocol Label Switching (MPLS) Layer 3 VPN; allows Layer 3 VPNs across a provider network
- MPLS and BGP integration; uses BGP to advertise routes across Label Switched Path (LSP)

# NetX X12 series

	NETX X1205	NETX X1220	NETX X1240	NETX X1260
<b>Performance</b>				
Overall performance	5 Gbps	20 Gbps	40 Gbps	60 Gbps
Routing table size	2,5 mil.	5 mil.	5 mil.	5 mil.
ARP table size	64 000	512 000	512 000	512 000
ND cache size	64 000	512 000	512 000	512 000
Supported VLANs	4096	4096	4096	4096
<b>Carrier Grade NAT sessions</b>				
	up to 5 mil.	up to 10 mil.	up to 20 mil.	up to 20 mil.
<b>Avg. power consumption</b>				
	60W	100W	150W	200W
<b>Ports</b>				
Network interfaces			2x 10G Base-T	
Expansion slots			2x	
Dedicated management			yes	
<b>Physical characteristics</b>				
Dimension		1U - 43.68 x 42.9 x 4.3 cm		
Weight		13 kg		
<b>Mounting and enclosure</b>				
		EIA-standard 19-inch rack		
<b>Electrical characteristics</b>				
Frequency and voltage		2x 230V / 50Hz, hot-swap		
Power supplies / efficiency		2x 400W / 94%		
<b>Environment</b>				
Operating temperature		5° - 35°		
Operating humidity		10% - 90% noncondensing		
<b>Dual flash memory</b>				
		yes		
<b>QoS</b>				
supported algorithms		HTB (Hierarchy Token Bucket), HSFC (Hierarchical Fair Service Curve), CoDEL, FQ_CoDEL, SFQ		

## Accessories

<b>Expansion slot cards</b>				
	NXB10 - 2x 10 Gb/s SFP+ ports NXB40 - 2x 40 Gb/s QSPF+ ports NXB100 - 2x 100 Gb/s QSPF28 ports			
<b>Support</b>				
	<b>NETX X1205 Series</b>		<b>NETX X1240 Series</b>	
	NXS1205A - 1-year Extended Warranty		NXS1240A - 1-year Extended Warranty	
	NXS1205B - 1-year Next Business Day On-site Service, Proactive Care & Online Monitoring		NXS1240B - 1-year Next Business Day On-site Service, Proactive Care & Online Monitoring	
	NXS1205C - 1-year Integration support		NXS1240C - 1-year Integration support	
	<b>NETX X1220 Series</b>		<b>NETX X2460 Series</b>	
	NXS1120A - 1-year Extended Warranty		NXS2460A - 1-year Extended Warranty	
	NXS1120B - 1-year Next Business Day On-site Service, Proactive Care & Online Monitoring		NXS2460B - 1-year Next Business Day On-site Service, Proactive Care & Online Monitoring	
	NXS1120C - 1-year Integration support		NXS2460C - 1-year Integration support	

## Standards and Protocols

applied to all products

<b>BGP</b>	RFC 4271 A Border Gateway Protocol 4 (BGP-4) RFC 1997 BGP Communities Attribute RFC 5492 Capabilities Advertisement with BGP-4 RFC 2385 BGP Session Protection via TCP MD5 RFC 4360 BGP Extended Communities Attribute RFC 4456 BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP) RFC 4724 Graceful Restart Mechanism for BGP	RFC 4272 BGP Security Vulnerabilities Analysis RFC 4274 BGP-4 Protocol Analysis RFC 4276 BGP-4 Implementation Report RFC 4277 Experience with the BGP-4 Protocol RFC 4451 BGP MULTI_EXIT_DISC (MED) Considerations RFC 5668 4-Octet AS Specific BGP Extended Community RFC 8092 BGP Large Communities Attribute RFC 7313 Enhanced Route Refresh Capability for BGP-4
<b>OSPF</b>	RFC 2328 OSPFv2 RFC 5340 OSPFv3 for IPv6 RFC 6987 OSPF Stub Router Advertisement RFC 6549 OSPFv2 Multi-Instance Extensions RFC 3101 OSPF NSSA	RFC 5187 OSPFv3 Graceful Restart RFC 3623 Graceful OSPF Restart RFC 4062 OSPF Benchmarking Terminology and Concepts RFC 4063 Considerations When Using Basic OSPF Convergence Benchmarks
<b>RIP</b>	RFC 1058 Routing Information Protocol RFC 2453 RIP Version 2	RFC 2080 RIPng for IPv6 RFC 4822 RIPv2 Cryptographic Authentication
<b>Babel</b>	RFC 6126 The Babel Routing Protocol	
<b>DDoS Protection</b>	RFC 5575 Dissemination of Flow Specification Rules RFC 7999 BLACKHOLE Community RFC 7674 Clarification of the Flowspec Redirect Extended Community	RFC 5635 Remote Triggered Black Hole Filtering with Unicast Reverse Path Forwarding (uRPF) RFC 6666 A Discard Prefix for IPv6
<b>IPv6</b>	RFC 2460 IPv6 Specification RFC 4443 ICMPv6 RFC 4861 IPv6 Neighbor Discovery RFC 4862 IPv6 Stateless Address Auto-configuration RFC 1981 Path MTU Discovery for IPv6 RFC 3315 Dynamic Host Configuration Protocol for IPv6 (DHCPv6) RFC 5722 Handling and Overlapping IPv6 Fragments RFC 5014 IPv6 Socket API for Source Address Selection	RFC 5095 Deprecation of Type 0 Routing Headers in IPv6 RFC 3736 Stateless DHCP Service for IPv6 RFC 4291 IP Version 6 Addressing Architecture RFC 3542 Advanced Sockets API for IPv6 RFC 6939 Client Link-Layer Address Option in DHCPv6 RFC 4251 SSHv6 Architecture RFC 4252 SSHv6 Authentication, Connection Transport Layer
<b>Network management</b>	IEEE 802.1AB Link Layer Discovery Protocol (LLDP) IEEE 802.1D (STP) RFC 1901 SNMPv2 Introduction RFC 1902 SNMPv2 Structure RFC 1903 SNMPv2 Textual Conventions RFC 1904 SNMPv2 Conformance RFC 1905 SNMPv2 Protocol Operations RFC 1906 SNMPv2 Transport Mappings RFC 3917 Requirements for IP Flow Information Export (IPFIX)	RFC 3176 sFlow® RFC 3954 Cisco Systems NetFlow Services Export Version 9 RFC 2272 SNMPv3 Management Protocol RFC 2570 SNMPv3 Overview RFC 2573 SNMPv3 Applications RFC 3411 SNMP Management Frameworks RFC 3412 SNMPv3 Message Processing RFC 3413 Simple Network Management Protocol (SNMP) Applications

## Standards and Protocols

applied to all products

---

### General protocols

RFC 2236 IGMP Snooping	RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)
RFC 3768 VRRP	RFC 2784 Generic Routing Encapsulation (GRE)
RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)	RFC 2865 Remote Authentication Dial In User Service (RADIUS)
RFC 3046 DHCP Relay Agent Information Option	RFC 2866 RADIUS Accounting
RFC 5880 Bidirectional Forwarding Detection	RFC 2868 RADIUS Attributes for Tunnel Protocol Support
RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)	RFC 2869 RADIUS Extensions
RFC 2993 Architectural Implications of NAT	RFC 2767 Dual Stacks IPv4 & IPv6
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)	RFC 768 UDP
IEEE 802.1Q VLANs	RFC 791 IP
IEEE 802.1Q CVRP	RFC 792 ICMP
IEEE 802.3ad Link Aggregation Control Protocol (LACP)	RFC 793 TCP
IEEE 802.3ae 10-Gigabit Ethernet	RFC 826 ARP
IEEE 802.3i 10BASE-T	RFC 856 TELNET
IEEE 802.3u 100BASE-X	RFC 894 IP over Ethernet
IEEE 802.3x Flow Control	RFC 2131 DHCP
	RFC 1631 NAT
	RFC 1305 NTPv3

---